

XS SERIES SPA PUMPS

XS-3C, XS-20, XS-30, XS-30S,
XS20-2S, XS30-2S, XS30-3P, XS-10B



KEY FEATURES



WIDESPREAD DISTRIBUTION

Fitted to most spas sold in Australia and New Zealand including Monarch, O2 Spas, Vortex, Oasis and Sapphire Spas brands.



AMP MATE-N-LOK CORDSETS

Equipped with 2 metre AMP over-moulded cordsets for direct connection to all XS and SV model spa controls.



2 YEAR WARRANTY

All XS series pumps and blowers are backed by SpaNET 2 year manufacturer warranty.

SPECIFICATIONS

	XS-3C	XS-20	XS-30	XS-30S
Power Supply	220-240V AC / 1PH / 50hz	220-240V AC / 1PH / 50hz	220-240V AC / 1PH / 50hz	220-240V AC / 1PH / 50hz
Wattage	250W	1500W	1850W	2200W
Horsepower	0.35HP	2.0HP	2.5HP	3.0HP
Rated Amperage	1.6A	7.0A	9.0A	10.0A
RPM	2900	2900	2900	2900
Capacitor	7uF / 450V	30uF / 450V	40uF / 450v	50uF / 450v
Maximum Flow (L/min)	170	620	670	730
Maximum Head (m)	7.5	14	16.0	18.0
Union Fittings	40mm (48.5mm ID)	50mm (60.3mm ID)	50mm (60.3mm ID)	50mm (60.3mm ID)
Environment Temp	40°C	40°C	40°C	40°C

	XS20-2S	XS30-2S	XS30-3P	XS10B
Power Supply	220-240V AC / 1PH / 50hz	220-240V AC / 1PH / 50hz	220/Y 380V / 3PH / 50hz	220-240V AC / 1PH / 50hz
Wattage	350W / 1500W	450W / 2200W	2200W	700W
Horsepower	0.4HP / 2.0HP	0.5HP / 3.0HP	3.0HP	1.0HP
Rated Amperage	2.0A / 7.0A	3.0A / 10.0A	9.2/Y 5.3A	4.0A
RPM	1450 / 2900	1450 / 2900	2900	-
Capacitor	30uF / 450v	40uF / 450v	-	-
Maximum Flow (L/min)	620	670	650	2.5m3/min
Maximum Head (m)	14.0	17.0	17.0	-
Union Fittings	50mm (60.3mm ID)	50mm (60.3mm ID)	50mm (60.3mm ID)	40mm (48.5mm ID)
Environment Temp	40°C	40°C	40°C	40°C